

((12) United States Patent Dreyer

(10) Patent No.:

US 6,527,097 B2

(45) Date of Patent:

Mar. 4, 2003

(54)	CONVEYOR IDLER			
(75)	Inventor:	Tertius F. Dreyer, Benoni (ZA)		
(73)	Assignee:	Rollerbrak (Proprietary) Limited, Heidelberg (ZA)		
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.		
(21)	Appl. No.: 09/999,181			
(22)	Filed:	Dec. 3, 2001		
(65)	Prior Publication Data			
	US 2002/0066648 A1 Jun. 6, 2002			
Related U.S. Application Data				
(63)	Continuation-in-part of application No. PCT/IB00/01571, filed on Oct. 31, 2000.			

(63)	Continuation-in-part of	application No.	PCT/IB00/01571,
	filed on Oct. 31, 2000.		

(30)Foreign Application Priority Data

(51)	Int. Cl. ⁷	B65G 13/00
(52)	U.S. Cl	193/35 A; 193/37; 193/35 R
(58)	Field of Search	74/577 M; 193/35 A,
	193/37, 35 R	: 198/781.01, 781.02, 781.03,

(ZA) 99/6862

781.04, 577

(56)References Cited

Nov. 2, 1999

U.S. PATENT DOCUMENTS

116,413 A	*	6/1871	Close 192/45
836,097 A	*	11/1906	Dann 192/45
842,841 A	*	1/1907	Starr 188/69
897,846 A	*	9/1908	Olds 192/45
1,273,952 A	*	7/1918	Tibbetts 192/113.1
1,362,011 A	*	12/1920	Kirby 192/45

1,437,718	Α		12/1922	Burns
2,060,376	Α	*	11/1936	Jex 188/30
2,085,271	Α	*	6/1937	Pfluger 192/105 CD
2,769,515	Α	*	11/1956	Thomas et al 192/45
3,012,645	Α	*	12/1961	Gensheimer 192/45
3,209,880	Α	*	10/1965	Dietiker 193/32
3,312,320	Α	*	4/1967	Froio 193/35 A
3,685,621	Α	*	8/1972	Gulick et al 192/12 B
3,713,521	Α	*	1/1973	Moritake 188/161
3,899,063	Α	*	8/1975	Pollard 188/130
3,918,561	Α	*	11/1975	Isacsson 188/184
4,548,316	Α	*	10/1985	Maurer 192/48.92
5,147,020	Α	*	9/1992	Scherman et al 188/382
5,253,856	Α	*	10/1993	Fuchi et al 198/570
6,131,717	Α	*	10/2000	Owen 188/82.1

FOREIGN PATENT DOCUMENTS

DE	864 978 C	1/1953
DE	32 45 347 A	5/1983

^{*} cited by examiner

Primary Examiner-Christopher P. Ellis Assistant Examiner—Richard Ridley (74) Attorney, Agent, or Firm-Nixon & Vanderhye, PC

ABSTRACT

A conveyor idler includes a sleeve having an outer surface and an inner surface, a shaft about which the sleeve can rotate in a forward direction, a locking mechanism for preventing the sleeve from rotating in a reverse direction, but which locking mechanism permits rotation of the sleeve in the forward direction, the locking mechanism being located within the sleeve and having a shaft member fixed to the shaft, with at least one locking member which can move between an unlocked position in which the sleeve can rotate in the forward direction and a locked position in which the locking member locks the sleeve to the shaft member to prevent rotation of the sleeve in the reverse direction.

18 Claims, 10 Drawing Sheets

